

Basket Strainers

It is generally accepted that the presence of foreign matter in fluid handling systems is highly undesirable and can lead to the premature failure of critical high value items of equipment, such as pumps and meters. The installation of Basket Strainers is therefore highly recommended and widely practised in these systems.

The Basket Strainers offer the end user a very low pressure loss under high flow conditions and an extended operational life. They are supplied with a quick release lid as standards, and this feature allows the basket to be removed quickly with no special tools, hence minimising the downtime during basket cleaning. Basket removal is possible without the unit being fully drained. The lid is sealed with an O-Ring which gives the lowest possible clamping force with no gaskets required, and there is a side drain point to allow rapid drainage of the contents.



Features

- Cast Carbon Steel Body
- Rugged High Strength Design
- Stainless Steel High Capacity Low Pressure Loss Basket
- Choice of Basket Mesh Sizes
- PED Compliant
- Quick Release Lid, no special tools required for Basket removal
- Side Drain Point
- O-Ring Lid Seal, No Gaskets
- Optional Differential Pressure Tapping
- Optional Automatic Air Vent Valve

Specifications


Standard:	PED/97/23/EC
Design Pressure:	20.0 BarG (290 psig)
Test Pressure:	29.5 BarG (428 psig) (refer to flange tables for temperature limitations)
Flanges:	ANSI B16.5 150lb raised face
External Finish:	Red oxide primer. Other paint finishes on request
Internal Finish:	Clean and oiled as standard Abrasive blasted and painted with Copon EA4/EA9 white epoxy lining on request



Basket Strainers

Ordering Information

Item	Material					
Strainer Body	ASTM A216 WCB					
Strainer Cover	ASTM A516 Gr60/A216 WCB					
Strainer Basket	Stainless Steel A316 40 mesh to 120 mesh					
Cover O-Ring	Viton A					
Vent Plug	ASTM A105N					
Drain Plug	ASTM A105N					
Strongback	ASTM A216 WCB					
Screw Handle	ASTM A193 B7M/St. Steel Handle					
Quick Release Pin	BS 970 080/M40 Zinc Plated					
Linch Pin	Carbon Steel Zinc Plated					



Part No	Size	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	Basket Area (sq. cm)	Vent ("NPT)	Drain ("NPT)	Nett Weight (kg)
6003073001	3"	365	570	40	342	410	375	652	3/8"	3/4"	47
6003074001	4"	445	695	47	426	505	450	1088	3/8"	1"	70
6003075001	6"	600	990	95	619	734	630	2151	1/2"	1.1/2"	167
6003083001	8"	715	1190	112	787	927	800	3973	1/2"	1.1/2"	310