







Liquip's SWIFT Delivery System is changing the way fuel deliveries are being made thanks to the most simple, yet technically advanced metering delivery system available on the market. The all-new SWIFT is noticeably lighter than conventional pumping systems, offering increased payload capacity. Backed by over 50 years of innovation, the SWIFT system is the **simplest, lightest, smartest** and **fastest** solution on the market today.



AT A GLANCE:



Gravity, Bulk and Hosereel deliveries (all metered)



Space and weight savings of an entire metering stream



One-touch level gauging of all compartments

I

Preset volumes for all delivery modes maximise flexibility



No flow rate restrictions, means quicker deliveries



User-friendly and reliable design with a familiar interface



NMI measurement and Zone 1 hazardous area safety approved



Australia-wide technical and support network

Swift Manifold eliminates spillage and product changeover times

SWIFT DELIVERY SYSTEM

DFV SWIFT Control Unit

- The industry's most technically advanced register and level-gauging in a combined unit
- Long service life with proven reliability and intuitive installation/programming/ operation
- Durable, lightweight aluminium housing built to withstand the harshest operating environments
- Piezoelectric buttons have no moving parts, allowing easy access for gloved hands
- Software upgrades can be performed quickly and easily





Swift Home Screen



Swift One-touch Compartment Level screen



DFV SWIFT Control Unit

- Simple to use with storage systems featuring 2 to 6 compartments
- Quick and easy installation with no need to open housing



DFV SWIFT Digital Display*

- 4" display with self-adjusting LED lighting for easy readability, even in direct sunlight
- IECEx and ATEX-approved for use in explosive areas and harsh environments

FEATURES & BENEFITS

- Metered gravity and bulk discharge
- Bulk discharge not restricted by equipment; over 1,000 L/ min (364 gpm)**
- Electronic register and Tank gauging in a combined unit
- NMI approved and meets AS2809
- Wetstock control accuracy to within ±0.5 mm, even on uneven ground

- Handles multi-product deliveries (Diesel and Petrol)
- Large digit LED display optional
- Can be loaded on uneven ground No inclination sensors required
- Clear operator prompts for quicker and simpler training of new or existing drivers
- Proven and trusted components with national parts availability and service support

- Incredible reliability means less downtime and the lowest whole-of-life-value cost
- Only one calibration needed for the life of the system
- Monitor level safely from ground
- Ability to split bulk tanker compartment deliveries
- Hazardous area approved for Zone 1 (IECEx)

INNOVATIVE TECHNOLOGY. CUSTOM SOLUTIONS.

Liquip has been engineering innovative cargo tank equipment for over 50 years. That experience and expertise has resulted in the most complete line of







cargo tank solutions on the planet. Simple or complex, Liquip's team has the knowledge and resources to deliver solutions that are engineered to your every need.

Swift Tanker System

- Liquip's SWIFT Delivery System was developed to be compatible with countless configurations.
- From compartment components to manifolds and controllers, Liquip designs custom configurations daily for customers worldwide.
- Work directly with Liquip team members to develop solutions that are engineered for you.

Swift Pump Module

- Compact design incorporates three individually measured outlets.
- Engineered to protect components while ensuing the elimination of air.
- Built with pneumatic actuators that automatically shut close if air loss occurs.

Hose Reels

- Liquip offers a full line of truck mounted hose reels.
- Tailored to suit customer's vehicles and maximize weight distribution.
- Built to last in the toughest of conditions, minimizing repair and replacement costs.

Distributed by:

Liquip International Pty Ltd

148 Newton Road, Wetherill Park · Sydney NSW Australia 2164 PO Box 7049 · Wetherill Park BC 2164 Tel: +61 2 9725 9000



